

Berth N0:1 Berth N0:2 Berth N0:2 Berth N0:2 Berth N0:3 Berth N0:4 Barge Berth Berth N0:5 Berth N0:6 Berth N0:7 Berth N0:7 Berth N0:9 Berth N0:10 Berth N0:10 Berth N0:12 Berth N0:12 WB 1 WB 2 WB 3 WB 4 3 WI ST CB 1 MICT CB 1 A 18 ACCE 18 ACC	295 185 230 230 85	Maximum Acceptable Beam	Maximum Acceptable Draft at CD. (*) (mtrs)	eclared on 31.° Displacement		Remark			
Berth NO:2 18 Berth NO:3 2: Berth NO:4 2: Barge Berth 8: Berth NO:5 30 Berth NO:6 30 Berth NO:7 2: Berth NO:9 2: Berth NO:10 2: Berth NO:10 2: Berth NO:11 2: Berth NO:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3	185 230 230				Remark				
Berth NO:2 18 Berth NO:3 2: Berth NO:4 2: Barge Berth 8: Berth NO:5 30 Berth NO:6 30 Berth NO:7 2: Berth NO:9 2: Berth NO:10 2: Berth NO:10 2: Berth NO:11 2: Berth NO:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	185 230 230		Terminal 1						
Berth No.3 22 Berth No.4 23 Berth No.5 30 Berth No.6 30 Berth No.7 22 Berth No.8 20 Berth No.10 22 Berth No.11 22 Berth No.11 22 Berth No.12 23 WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	230 230	7.5	13.6	90000					
Berth N0:4 2: Barge Berth 8: Berth N0:5 30 Berth N0:6 30 Berth N0:7 2: Berth N0:8 20 Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	230	رر	13.8	40000					
Berth N0:5 30 Berth N0:6 30 Berth N0:7 2: Berth N0:8 20 Berth N0:9 2: Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3		45	14.2	90000					
Berth N0:5 30 Berth N0:6 30 Berth N0:7 20 Berth N0:8 20 Berth N0:9 20 Berth N0:10 20 Berth N0:11 20 Berth N0:12 20 WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	85	35	14	90000					
Berth N0:6 30 Berth N0:7 2: Berth N0:8 20 Berth N0:9 2: Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3		15	6	4200					
Berth N0:6 30 Berth N0:7 2: Berth N0:8 20 Berth N0:9 2: Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3				Terminal	2				
Berth N0:7 2: Berth N0:9 2: Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	300	45	14.2	180000	Total Quay length 575 mtrs hence more than two ships can be berthed in each quay subject to 35 mtrs clearance between ships. Total Quay length 441 mtrs hence more than two ships can be berthed in each quay subject to 35 mtrs clearance between ships.				
Berth N0:9 2: Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	300	45	15.5	180000					
Berth NO:9 2: Berth NO:10 2: Berth NO:11 2: Berth NO:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	225	35	11.8	63000					
Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	200	35	9.6	63000					
Berth N0:10 2: Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	T			Terminal	3				
Berth N0:11 2: Berth N0:12 2: WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	295	48	13.4	120000	Total Ourselesses	794 mtrs hance more than two ships and he hosting in			
WB 1 3 WB 2 3 WB 3 WB 4 3 WB 4 3	295	48	13.2	74000		n 794 mtrs hence more than two ships can be berthed in tt to 35 mtrs clearance between ships.			
WB 1 3 WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3	295	48	13	74000					
WB 2 3 WB 3 3 WB 4 3	235	35	12.8	74000					
WB 2 3 WB 3 3 WB 4 3 MICT CB 1 3				West Bas	in				
WB 3 3 3 WB 4 3 MICT CB 1 3	325	55	17.5	266000					
WB 4 3	325	55	17.5	266000					
MICT CB 1 3	325	55	17.5	266000					
	325	55	16.5	321000					
				Container Ter	minal	T			
MICT CB 2	365	55	15.4	180000	Only up to	ard 32 I of all quay length of each terminal 530 meters each in straight line and hence more than two ships can be berthe in each terminal subject to a minimum of 35 mtrs clearanc between each yessel			
	365	55	15.4	180000	bollard 32				
AMCT CB 3	365	55	15.5	180000	Only up to				
AMCT CB 4	365	55	15.5	180000	bollard 31				
ACMTPL SB4 4	405	60	16.2	231600		al quay length 650 mtrs in straight line hence more than two ships can b thed in each quay subject to 35 mtrs clearance between ships.			
ACMTPL SB5 4	405	60	16.2	231600	berthed in each o				
AICTPL SB6 4	405	60	16.1	180000					
AICTPL SB7 4	405	60	16.2	180000	Total quay length 1460 mtrs in straight line hence more than four ships can be berthed in each quay subject to 35 mtrs clearance between ships.				
AICTPL SB8 4	405	60	16.1	231600					
	405	60	15		<u> </u>				
AICTPL 3B9 4	405		19	231600					
LNG Terminal									
LNG 4	410	55	15.2	178578					
NOTE: 1. All de	1. All depths are in meters and below chart datum (i.e, 0.0 mtrs height of tide)								
Maximum acceptable draft at CD for a berth is basis the Lowest Astronomical Tide which is 0.0 mtrs. Higher berthing draft may be accepted basis the low water expected during the vessel stay at the berth. For Example: If the Maximum acceptable draft for a given berth at CD is given as 13 metres and the height of lowest low water expected during the vess stay is 0.5 metres, then maximum acceptable draft for that berth will be 13.5 metres.									
							4. A Mii maintai	4. A Minimum under keel clearance of 10% of the ship's draft" will be maintained during channel passage. A minimum UKC of 0.3 to 0.5 mtrs will be maintained at all time when the vessel is alongside the berth.	
 Minimum depth in approach channel and manoeuvring basin for the month is as follows. a) MICT approach channel - 13.8 mtrs. b) South basin (AI ACMPTL) approach channel - 14.70 mtrs c) West basin approach channel - 14.6 mtrs. 									
AMCT a South B West Ba	6.Drafts at which vessel can sail anytime (AMCT/MICT/SB/WB) Lowest Low water in 02nd Jan: 0.55 mtrs. AMCT and MICT South Basin (AICTPL & ACMPTL): vessels with draft < = 13.68 M can sail anytime. vessels with draft < = 13.69 M can sail anytime. vessels with draft < = 13.69 M can sail anytime. Above drafts are basis 10% UKC in the channel. 7. (a) Max acceptable LOA / Beam / Draft for IOCL SPM is 348 / 65 / 25 Mtrs (b) Max acceptable LOA / Beam / Draft for HMEL SPM is 345 / 60 / 23 Mtrs (c) Night berthing is restricted at both IOCL and HMEL SPM 8. Weather Parameters for berth (a) Cease berthing activity when sustained wind speed more than 30 kts. (b) Cease cargo transfer operation when sustained wind speed more than 35 kts. (c) Unberth ship if sustained when wind speed more than 40 kts.								
(b) N									
(a) C (b) C									
					nsoon period. Remai	ining part of the year it ranges between 1.024 to 1.025			

Capt. Sachin Srivastava Head - Marine Services

Adani Ports and Special Economic Zone Ltd Adani House P.O. Box 1 Mundra, Kutch 370 421 Gujarat, India

Tel +91 02838 255781 Fax +91 2838 25 5110 info@adani.com www.adaniports.com

Registered Office: "Adani Corporate House", Shantigram, Near Vaishno Devi Circle, S. G. Highway, Ahmedabad - 382421, Gujarat, India.