

Declared on 01.09.2022

Berth	Maximum Acceptable LOA	Maximum Acceptable Beam	Maximum Acceptable Draft at CD. (*) (mtrs)	Displacement	Remark
Terminal 1					
Berth NO:1	295	48	13.5	90000	
Berth NO:2	185	35	14.1	40000	
Berth No.3	230	45	14.2	90000	
Berth NO:4	230	35	14.0	90000	
Barge Berth	85	15	6.0	4200	
Terminal 2					
Berth NO:5	300	45	13.8	180000	Total Quay length 575 mtrs hence more than two ships can be berthed in each quay subject to 35 mtrs clearance between ships.
Berth NO:6	300	45	14.6	180000	
Berth NO:7	225	35	Berth 7 and Berth 8 are Non Operational		
Berth NO:8	200	35			
Terminal 3					
Berth NO:9	295	48	13.4	120000	Total Quay length 794 mtrs hence more than two ships can be berthed in each quay subject to 35 mtrs clearance between ships.
Berth NO:10	295	48	13.3	74000	
Berth NO:11	295	48	13.1	74000	
Berth NO:12	235	35	13.0	74000	
West Basin					
WB 1	325	55	17.5	266000	
WB 2	325	55	17.5	266000	
WB 3	325	55	17.5	266000	
WB 4	325	55	16.2	321000	
Container Terminal					
MICT CB 1	365	55	14.8	180000	Only up to bollard 32
MICT CB 2	365	55	14.8	180000	
AMCT CB 3	365	55	14.8	180000	Only up to bollard 31
AMCT CB 4	365	55	14.8	180000	
ACMTPS SB4	405	60	15.8	231600	Total quay length 650 mtrs in straight line hence more than two ships can be berthed in each quay subject to 35 mtrs clearance between ships.
ACMTPS SB5	405	60	15.8	231600	
AICTPL SB6	405	60	15.5	180000	Total quay length 1460 mtrs in straight line hence more than four ships can be berthed in each quay subject to 35 mtrs clearance between ships.
AICTPL SB7	405	60	15.6	180000	
AICTPL SB8	405	60	15.3	231600	
AICTPL SB9	405	60	14.5	231600	
LNG Terminal					
LNG	410	55	15.1	178578	
NOTE:	<p>1. All depths are in meters and below chart datum (i.e. 0.0 mtrs height of tide)</p> <p>2. Maximum acceptable draft at CD for a berth is basis the Lowest Astronomical Tide which is 0.0 mtrs.</p> <p>3. Higher berthing draft may be accepted basis the low water expected during the vessel stay at the berth. For Example: If the Maximum acceptable draft for a given berth at CD is given as 13 metres and the height of lowest low water expected during the vessel's stay is 0.5 metres, then maximum acceptable draft for that berth will be 13.5 metres.</p> <p>4. A Minimum under keel clearance of 10% of the ship's draft* will be maintained during channel passage. A minimum UKC of 0.3 to 0.5 mtrs will be maintained at all time when the vessel is alongside the berth.</p> <p>5. Minimum depth in approach channel and manoeuvring basin for the month is as follows. a) MICT approach channel - 13.7 mtrs. b) South basin (AICTPL & ACMPTL) approach channel - 14.6 mtrs c) West basin approach channel -14.6 mtrs.</p> <p>6. Drafts at which vessel can sail anytime (AMCT/MICT/SB/WB) Lowest Low water in 10th Sep : 0.84 mtrs. AMCT and MICT : Vessels with draft < = 13.22 M can sail anytime. South Basin (AICTPL & ACMPTL) : vessels with draft < = 14.00 M can sail anytime. West Basin : vessels with draft < = 14.00 M can sail anytime (Sub to Tidal Window) Above drafts are basis 10% UKC in the channel.</p> <p>7. (a) Max acceptable LOA / Beam / Draft for IOCL SPM is 348 / 65 / 25 Mtrs (b) Max acceptable LOA / Beam / Draft for HMEL SPM is 345 / 60 / 23 Mtrs (c) Night berthing is restricted at both IOCL and HMEL SPM</p> <p>8. Weather Parameters for berth (a) Cease berthing activity when sustained wind speed more than 30 kts. (b) Cease cargo transfer operation when sustained wind speed more than 35 kts. (c) Unberth ship if sustained when wind speed more than 40 kts.</p> <p>9. Water Density - Water Density varies from 1.020 to 1.023 during SW Monsoon period. Remaining part of the year it ranges between 1.024 to 1.025</p>				

Thanking you



Capt. Sachin Srivastava
Head - Marine Services

Adani Ports and Special Economic Zone Ltd
Adani House
P.O. Box 1
Mundra, Kutch 370 421
Gujarat, India

Tel +91 02838 255781
Fax +91 2838 25 5110
info@adani.com
www.adaniports.com

Registered Office: "Adani Corporate House", Shantigram, Near Vaishno Devi Circle, S. G. Highway, Ahmedabad - 382421, Gujarat, India.